

NTH 3000-PH63

Acid condensate neutralizer with pump












A control unit activates the pump through probes. An external system signals the station status and through this system allows manual tests on the working pump.

The neutralizer station of acid condensate with the pump is easy to be installed and allows the evacuation of condensate when it is not possible to discharge for gravity. The strong structure of the tankand the pump NTH3000 make this product reliable. The recharge and the maintenance are easy and fast.

Code	Article	Description
SP040PH3001	NTH 3000-PH63	Neutralizer station with pump
SPN0409063	NEUTRALKIT63	Granular Neutralkit



Technical data	
Max generator power	2600 kW
Max flow	260 l/h
Minimum inlet head	130 mm
Voltage	220V - 50Hz
Absorption	60W
Max head	3,2 m
Max flow rate	3.000 l/h
Dimensions	
Weight	
Non return valve included	
Long-life at max flow	1100 h

Ref.	Description	Exar
1	Inlet connection G 1"1/4	Exai
2	Neutralizer granular refill Neutralkit	1 - W
3	Inlet filter T Shape	standi
4	Neutralizer box	The
6	Outlet connection G 1/2"	install and in
7	Submerged pump	The in
		given office — 6

mple of installation

vall-mounted or floor ling boilers

station has to be lled near the boiler in horizontal position. nlet pipe to the station follow the guide lines by our technical

